

BL AIR SIDE 600

BLA23S0600024DC13867840000W05

Article no.: 102125

BILTON
FOCUSED
ON
LINEAR
LIGHT



24
V

Lamp voltage

600
lm

Luminous flux per meter

5010.0
mm

Max. length

>80

Colour rendering index CRI

TENDER TEXT

BL AIR SIDE 600 LED strip 24VDC 13,8W/m IP67 CRI>80 4000K WHITE 5m LED module
BL AIR SIDE 600 Article 102125 Linear LED light strip on a flexible circuit board. Installation using appropriate mounting accessories in conjunction with Plug-&-Play connection system. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +55 °C at a service life of 50000 h . At an ambient temperature of 85°C, a lifetime of 50,000 hours can still be guaranteed. Up to 95°C the lifetime is 30,000 hours and at temperatures of 100°C still 16,000 hours (> L70B50). The BL AIR SIDE 600 LED-strip has a luminous flux of 600 lm at 13.8 W, resulting in an efficiency of 43 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 5010.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 4000 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IP67 Smallest possible bending radius 200 mm Dimension (L x W x H): 5010.0 mm x 13.2 mm x 16.0 mm

TOP-FEATURES

- //_ Homogeneously luminous light line without visible light points
- //_ IP67 -protection in highly flexible silicone jacket
- //_ UL certified
- //_ New connection: the end caps close straight to the profile


BL AIR SIDE 600

BLA23S0600024DC13867840000W05

Article no.: 102125

BILTON

FOCUSED
ON
LINEAR
LIGHT



BL AIR SIDE 600

BLA23S0600024DC13867840000W05

Article no.: 102125

MECHANICAL DATA

Net width [mm]	13.2
Net height [mm]	16.0
Net length [mm]	5010.0
Degree of protection (IP)	IP67
Colour	White
Distance [mm]	7.14
Distance relating to	LED to LED
Length of particular segments [mm]	50.0

ELECTRICAL DATA

Overall efficiency [lm/W]	43
Lamp power per meter [W]	13.8
Lamp voltage [V]	24
Input voltage range [V]	23 - 25
Voltage type	DC
Protection class	III

LIGHT TECHNICAL DATA

Luminous flux per meter [lm]	600
Beam angle [°]	120
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	>80
Colour temperature [K]	4000

CONNECTION

Number of poles	2
Conductor cross section [mm ²]	0.50
Max. length [mm]	5010.0

TEMPERATURE TECHNICAL DATA

Rated life time L80/B10 at 25 °C [h]	50000
Ambient temperature during operating [°C]	- 20 ... + 55
Ambient/storage temperature [°C]	- 20 ... + 55

PACKAGING INFORMATION

EAN	4250716944600
Article no.	102125
Customs tariff number	94054039
Length [mm]	5010.0

BL AIR SIDE 600

BLA23S0600024DC13867840000W05

Article no.: 102125

Gross weight [g]	0.6
Gross height [mm]	27.0
Gross width [mm]	330.0
Gross length [mm]	330.0
State of origin	AT

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com