BL ONE XTreme DUAL-S 2000 >80

BILTON
FOCUSED ON LINEAR LIGHT

BLDUS2000024DC16020830000W05
Article no.: 100066

BILTON LEDON
BETTER LIGHT

Oops – erwischt!

Hier folgt bald das gewünschte Bild.

24 V	**1910** lm	**5000.0** mm	**>80**
Lamp voltage	Luminous flux per meter	Max. length	Colour rendering index CRI

TENDER TEXT

BL DUAL SAFETY 2000 LED strip 24VDC 16W/m IP20 CRI>80 3000K WHITE 5m

TOP-FEATURES

//__ Doubles the life cycle thanks to double and independent LED channels

//__ doubles the life of 60000 h

//__ Developed and produced in Austria by BILTON LEDONDeveloped and produced in Austria by BILTON LEDON

| 24 V | >80 | IP20 | 3000 K | RoHS COMPLIANT 2002/95/EC | CE | M |

# BL ONE XTreme DUAL-S 2000 >80

BLDUS2000024DC16020830000W05
Article no.: 100066

MECHANICAL DATA

Net width [mm]	12.0
Net height [mm]	1.5
Net length [mm]	5040.0
Degree of protection (IP)	IP20
Distance [mm]	4.29
Distance relating to	LED zu LED
Length of particular segments [mm]	60.0

ELECTRICAL DATA

Overall efficiency [lm/W]	119
Lamp power per meter [W]	16.0
Lamp voltage [V]	24
Imput voltage range [V]	23 - 25
Voltage type	DC
Protection class	III

LIGHT TECHNICAL DATA

Luminous flux per meter [lm]	1910
Beam angle [°]	120
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	>80
Colour temperature [K]	3000

CONNECTION

Number of poles	2
Conductor cross section [mm²]	0.50
Max. length [mm]	5000.0

TEMPERATURE TECHNICAL DATA

Rated life time L70/B10 at 25 °C [h]	60000
Ambient temperature during operating [°C]	- 20 ... + 45

PACKAGING INFORMATION

EAN	4250716943948
Article no.	100066
Customs tariff number	94054099
Length [mm]	5040.0
Gross weight [g]	0.0
Gross height [mm]	22.0

BL ONE XTreme DUAL-S 2000 >80

BLDUS2000024DC16020830000W05

Article no.: 100066

Gross width [mm]	200.0
Gross length [mm]	200.0
State of origin	AT

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com