


BLOHE 900 >90

BLOHE0900024DC05620927000W20

Article no.: 102164

BILTON

FOCUSED
ON
LINEAR
LIGHT




Lamp voltage



Luminous flux per meter



Max. length



Colour rendering index CRI

TENDER TEXT

BL ONE High Efficiency LED strip 900 24VDC 5,6W/m IP20 CRI>90 2700K WHITE 20m LED module BLOHE 900 >90 Article 102164 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h . The BLOHE 900 >90 LED-strip has a luminous flux of 880 lm at 5.6 W, resulting in an efficiency of 157 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 6000.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 2700 K and a beam angle of 120°. All this with a colour rendering index of >90 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 6.25 mm. Degree of protection IP20 Dimension (L x W x H): 20000.0 mm x 8.0 mm x

TOP-FEATURES

- //_ Improvement of homogeneity by 20 additional LEDs per meter
- //_ Wide choice of light colors and lumen packages
- //_ Wide range of applications for linear lighting in white
- //_ With a maximum module length of up to 6000.0 mm long, linear lighting lines can be implemented



BLOHE 900 >90

BLOHE0900024DC05620927000W20

Article no.: 102164

MECHANICAL DATA

Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	20000.0
Degree of protection (IP)	IP20
Net weight [g]	199
Distance [mm]	6.25
Distance relating to	LED to LED
Length of particular segments [mm]	50.0

ELECTRICAL DATA

Overall efficiency [lm/W]	157
Lamp power per meter [W]	5.6
Lamp voltage [V]	24
Input voltage range [V]	23 - 25
Voltage type	DC
Protection class	III

LIGHT TECHNICAL DATA

Luminous flux per meter [lm]	880
Beam angle [°]	120
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	>90
Colour temperature [K]	2700
Energy efficiency class provided exchangeable built-in lamp	D

CONNECTION

Number of poles	2
Conductor cross section [mm ²]	0.50
Max. length [mm]	6000.0

TEMPERATURE TECHNICAL DATA

Rated life time L80/B10 at 25 °C [h]	60000
Ambient temperature during operating [°C]	- 20 ... + 45
Ambient/storage temperature [°C]	- 5 ... + 55
Operation temperature at Tc [°C]	- 5 ... + 60

PACKAGING INFORMATION

EAN	4250716945959
Article no.	102164

BLOHE 900 >90

BLOHE0900024DC05620927000W20

Article no.: 102164

Length [mm]	20000.0
Gross weight [g]	319.0
Gross height [mm]	18.0
Gross width [mm]	200.0
Gross length [mm]	200.0
State of origin	AT

* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 °C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com