

BLRET 3000



BLRET3000024DC277X6935000W05

Article no.: 101846

BILTON

FOCUSED
ON
LINEAR
LIGHT

CRI
>95



Lamp voltage



Luminous flux per meter



Max. length



Colour rendering index CRI

TENDER TEXT

BL RETAIL 3000 LED strip 24VDC 27,7W/m IPX6 CRI>95 3500K WHITE 5m LED module BLRET 3000 Article 101846 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h. The BLRET 3000 LED-strip has a luminous flux of 2770 lm at 27.7 W, resulting in an efficiency of 100 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 4500.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 3500 K and a beam angle of 120°. All this with a colour rendering index of >95 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IPX6 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.5 mm

TOP-FEATURES

- //__ Best light quality for shop lighting thanks to CRI >95
- //__ Long line lengths and better stability due to double layer
- //__ Wide choice of light colors and lumen packages
- //__ Available in Degree of Protection IPX6
- //__ UL certification available



BLRET 3000

BLRET3000024DC277X6935000W05

Article no.: 101846

MECHANICAL DATA

| | |
|------------------------------------|------------|
| Net width [mm] | 8.0 |
| Net height [mm] | 1.5 |
| Net length [mm] | 5000.0 |
| Degree of protection (IP) | IPX6 |
| Colour | White |
| Distance [mm] | 7.14 |
| Distance relating to | LED to LED |
| Length of particular segments [mm] | 50.0 |

ELECTRICAL DATA

| | |
|---------------------------|---------|
| Overall efficiency [lm/W] | 100 |
| Lamp power per meter [W] | 27.7 |
| Lamp voltage [V] | 24 |
| Input voltage range [V] | 23 - 25 |
| Voltage type | DC |
| Protection class | III |

LIGHT TECHNICAL DATA

| | |
|---|-------|
| Luminous flux per meter [lm] | 2770 |
| Beam angle [°] | 120 |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Colour rendering index CRI | >95 |
| Colour temperature [K] | 3500 |
| Energy efficiency class provided exchangeable built-in lamp | F |

CONNECTION

| | |
|--|--------|
| Number of poles | 2 |
| Conductor cross section [mm ²] | 0.50 |
| Max. length [mm] | 4500.0 |

TEMPERATURE TECHNICAL DATA

| | |
|---|---------------|
| Rated life time L80/B10 at 25 °C [h] | 60000 |
| Ambient temperature during operating [°C] | - 20 ... + 45 |
| Ambient/storage temperature [°C] | - 5 ... + 55 |
| Operation temperature at Tc [°C] | - 5 ... + 60 |

PACKAGING INFORMATION

| | |
|-------------|---------------|
| EAN | 4250716936018 |
| Article no. | 101846 |

BLRET 3000

BLRET3000024DC277X6935000W05

Article no.: 101846

| | |
|-----------------------|----------|
| Customs tariff number | 94054099 |
| Length [mm] | 5000.0 |
| Gross weight [g] | 0.0 |
| Gross height [mm] | 18.0 |
| Gross width [mm] | 200.0 |
| Gross length [mm] | 200.0 |
| State of origin | AT |

* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com