

CASAMBI PWM4 dimmer

BILTON

FOCUSED
ON
LINEAR
LIGHT

BL Casambi Dimmer 4CH PWM constant voltage

Article no.: 170924



Control signal

TENDER TEXT

1-4 channel LED dimmer for constant voltage 24VDC. Maximum total output 144W at 24VDC (max. 6A). Input voltage 12-24VDC. Radio control signal. PWM frequency 400Hz. Protection class IP20. Protection class III. dimensions LxWxH = 72.6x30x18mm BILTON LEDON TechnologyCASAMBI PWM4 dimmer Article 170924 The controller CASAMBI PWM4 dimmer is operated with Radio frequency (RF) and is served with a Radio frequency (RF) . The controller and has an output voltage of 12-24VDC V .The power dissipation in stand-by is . Dimension (L x W x H): 72.6 mm x 30.0 mm x 18.0 mm

TOP-FEATURES

//_ Remote radio control for switching, dimming and controlling BILTON LEDON Technology RGB modules

//_ Remote control incl. receiver (control)

Radio
frequency
(RF)



CASAMBI PWM4 dimmer

BILTONFOCUSED
ON
LINEAR
LIGHT

BL Casambi Dimmer 4CH PWM constant voltage

Article no.: 170924

MECHANICAL DATA

Net width [mm]	30.0
Net height [mm]	18.0
Net length [mm]	75.0
Colour	White
Mounting method	Other
Surface protection	Untreated
Net weight [g]	45.1
Material	Plastic

ELECTRICAL DATA

Control signal	Radio frequency (RF)
----------------	----------------------

PACKAGING INFORMATION

EAN	4250716942033
Article no.	170924
Customs tariff number	8536500500
Gross weight [g]	45.9
Gross height [mm]	19.0
Gross width [mm]	100.0
Gross length [mm]	140.0
State of origin	FI

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com