RGBW Controller

BL control unit RGBW 12-48VDC 480W for LED strip IP20 wireless incl. FB Article no.: 171215







TENDER TEXT

1-4 channel LED dimmer for constant voltage 24VDC. Maximum total output 480W at 24VDC (max. 20A). Input voltage 12-48VDC. Radio control signal. Protection class IP20. Protection class III. dimensions LxWxH = 175x45x27mm BILTON LEDON TechnologyRGBW Controller Article 171215 The controller RGBW Controller is operated with Radio frequency (RF) and is served with a Radio frequency (RF). The controller and has an output voltage of 24 V. The power dissipation in stand-by is . Dimension (L x W x H): 175.0 mm x 45.0 mm x 27.0 mm

TOP-FEATURES

 $\prime\prime_$ Remote radio control for switching, dimming and controlling BILTON LEDON Technology RGB and RGBW modules

//__ Remote control incl. receiver (control)

Radio frequency (RF)

RGBW Controller

BL control unit RGBW 12-48VDC 480W for LED strip IP20 wireless incl. FB Article no.: 171215



MECHANICAL DATA

Material Plastic	

ELECTRICAL DATA

Control signal	Radio frequency (RF)
Imput voltage range [V]	3,5 - 7
Voltage type	DC
Number of channels	4

TEMPERATURE TECHNICAL DATA

|--|

PACKAGING INFORMATION

EAN	4250716942071
Article no.	171215
Customs tariff number	85437090
Gross weight [g]	0.1
State of origin	CN

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com

© BILTON International GmbH, Gewerbepark Harham 2, 5760 Saalfelden, Austria // Phone: +43 6582 71164 // Mail: office@bltechnology.at // www.biltongroup.com