


BL COR Pure Free 1300

BL COR PURE Free LED strip 1285lm/m 24VDC 9.6W/m IP20 927 5m

Article no.: 171854



Length of particular segments



Distance



Distance relating to

TENDER TEXT

LED strip light Freecut 1285 lm/m 24VDC 9.6W/m 134lm/W IP20 CRI>90 2700K; Separability 8.33 mm; one-sided connection cable 50 cm, WHITE Colors and BLT label 5 meters LED module BL COR Pure Free 1300 Article 171854 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Suitable for ambient temperatures from -25 ... +40 °C at a service life of 60000 h . The BL COR Pure Free 1300 LED-strip has a luminous flux of 1285 lm at 9.6 W, resulting in an efficiency of 134 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 5000.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 2700 K and a beam angle of 119°. All this with a colour rendering index of >90 and a Binning selection based on (MacAdams). The light strip can be separated every 8.3 mm, resulting in a LED distance of 8.33 mm. Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.5 mm

TOP-FEATURES

- //_ LED strip, all 8.3 mm separable
- //_ Without soldering connection
- //_ 24 V-Single LED per cut for more flexible application

24 V	>90	IP20	2700 K
------	-----	------	--------

BL COR Pure Free 1300

BL COR PURE Free LED strip 1285lm/m 24VDC 9.6W/m IP20 927 5m

Article no.: 171854

MECHANICAL DATA

Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	5000.0
Degree of protection (IP)	IP20
Colour	White
Net weight [g]	135
Distance [mm]	8.33
Distance relating to	LED to LED
Length of particular segments [mm]	8.3

ELECTRICAL DATA

Overall efficiency [lm/W]	134
Lamp power per meter [W]	9.6
Lamp voltage [V]	24
Input voltage range [V]	23 - 25
Voltage type	DC
Protection class	III

LIGHT TECHNICAL DATA

Luminous flux per meter [lm]	1285
Beam angle [°]	119
Colour rendering index CRI	>90
Colour temperature [K]	2700

CONNECTION

Number of poles	2
Max. length [mm]	5000.0

TEMPERATURE TECHNICAL DATA

Rated life time L70/B50 at 25 °C [h]	60000
Ambient temperature during operating [°C]	- 25 ... + 40

PACKAGING INFORMATION

EAN	4250716948721
Article no.	171854
Customs tariff number	9405423990
Length [mm]	5000.0
State of origin	CN

BL COR Pure Free 1300

BILTONFOCUSED
ON
LINEAR
LIGHT**BL COR PURE Free LED strip 1285lm/m 24VDC 9.6W/m IP20 927 5m**

Article no.: 171854

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com