

BL MW Power supply unit CV 90-305VAC 40W 24VDC 1600mA IP67

Article no.: 170200





Output voltage range



Output power range



TENDER TEXT

Constant voltage power supply unit. Input voltage 90-305VAC. Maximum total power 40W (max. 1.6A). Output voltage 24VDC. Protection class IP67. Protection class I. Dimensions LxWxH = 171x61.5x36.8mm BILTON LEDON Technology power supply BLPSI 35 Article 170200 The power supply can be used up to 40 W output power and 24 V output voltage. The supply voltage of the power supply is 90 - 305 V and has a IP67 protection class and protection class III . Dimension (L x W x H): 171.0 mm x 61.5 mm x 36.8 mm











BLPSI 35



BL MW Power supply unit CV 90-305VAC 40W 24VDC 1600mA IP67

Article no.: 170200

MECHANICAL DATA

Net width [mm]	50.0
Net height [mm]	40.0
Net length [mm]	150.0
Degree of protection (IP)	IP67
Housing	Metal housing
Net weight [g]	670

ELECTRICAL DATA

Control signal	None
Imput voltage range [V]	90 - 305
Voltage type	AC
Output power range [W]	40
Output voltage range [V]	24
With overheating protection	yes
Overload protection	yes
Output current range [mA]	1600
Protection class	III

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature [°C]	- 40 + 80
Operation temperature at Tc [°C]	- 40 + 80
Lifespan at 20 °C [h]	60000

PACKAGING INFORMATION

EAN	4250716917390
Article no.	170200
Customs tariff number	85043180
Length [mm]	171.0
Gross weight [g]	700.0
Gross height [mm]	50.0
Gross width [mm]	80.0
Gross length [mm]	220.0
State of origin	CN

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com