

Article no.: 170201



Output voltage range



Output power range



Degree of protection (IP)

Constant voltage power supply unit. Input voltage 90-305VAC. Maximum total power 60W (max. 2.5A). Output voltage 24VDC. Protection class IP67. Protection class I. Dimensions LxWxH = 171x61.5x36.8mm BILTON LEDON Technology power supply BLPSI 60 Article 170201 The power supply can be used up to 60 W output power and 24 V output voltage. The supply voltage of the power supply is 90 - 305 V and has a IP67 protection class and protection class III . Dimension (L x W x H): 171.0 mm x 61.5 mm x 36.8 mm



MECHANICAL DATA

Net width [mm]	50.0
Net height [mm]	40.0
Net length [mm]	150.0
Degree of protection (IP)	IP67
Housing	Metal housing
Net weight [g]	660

ELECTRICAL DATA

Control signal	None
Input voltage range [V]	90 - 305
Voltage type	AC
Output power range [W]	60
Output voltage range [V]	24
With overheating protection	yes
Overload protection	yes
Output current range [mA]	2500
Protection class	III

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature [°C]	- 40 ... + 80
Operation temperature at Tc [°C]	- 40 ... + 80
Lifespan at 20 °C [h]	60000

PACKAGING INFORMATION

EAN	4250716936612
Article no.	170201
Customs tariff number	85043180
Length [mm]	171.0
Gross weight [g]	700.0
Gross height [mm]	50.0
Gross width [mm]	80.0
Gross length [mm]	220.0
State of origin	CN

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com