


# BL COR Pure 900

DJ120, 3000K, CRI80, 8.8W, 24V, IP20, 50m

Article no.: 171561

**BILTON**

FOCUSED  
ON  
LINEAR  
LIGHT



Lamp voltage



Luminous flux per meter



Max. length



Colour rendering index CRI

## TENDER TEXT

DJ120-24V-8mm 8,8W/M1000LM/M CRI80 3000K IP20, 50m/electrian box



# BL COR Pure 900

DJ120, 3000K, CRI80, 8.8W, 24V, IP20, 50m

Article no.: 171561

**BILTON**

FOCUSED  
ON  
LINEAR  
LIGHT

## MECHANICAL DATA

Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	50000.0
Degree of protection (IP)	IP20
Colour	White
Net weight [g]	920
Distance [mm]	8.33
Distance relating to	LED to LED
Length of particular segments [mm]	50.0

## ELECTRICAL DATA

Overall efficiency [lm/W]	100
Lamp power per meter [W]	9.6
Lamp voltage [V]	24
Voltage type	DC
Protection class	III

## LIGHT TECHNICAL DATA

Luminous flux per meter [lm]	960
Beam angle [°]	117
Colour rendering index CRI	>80
Colour temperature [K]	3000

## CONNECTION

Number of poles	2
Max. length [mm]	50000.0

## TEMPERATURE TECHNICAL DATA

Rated life time L80/B50 at 25 °C [h]	36000
Ambient temperature during operating [°C]	- 25 ... + 40
Ambient/storage temperature [°C]	0 ... + 60

## PACKAGING INFORMATION

EAN	4250716948592
Article no.	171561
Customs tariff number	9405423990
Length [mm]	50000.0
State of origin	CN

# BL COR Pure 900

**DJ120, 3000K, CRI80, 8.8W, 24V, IP20, 50m**

Article no.: 171561

**BILTON**

FOCUSED  
ON  
LINEAR  
LIGHT

\* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.biltongroup.com](http://www.biltongroup.com)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.biltongroup.com](http://www.biltongroup.com)